



Image shown may not reflect actual package.

STANDBY 750 kW 937 kVA 60 Hz 1800 rpm 480 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers fill 99.7% of parts orders within 24 hours
- Caterpillar dealers have over 1,844 dealer branch stores operating in 166 countries
- The Cat Scheduled Oil Sampling (S•O•SSM) program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested

ENCLOSURES (optional)

- Weather protective and sound attenuated

CAT® 3412C TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight
- UL 2200 Listed packages are available. Certain restrictions may apply. Consult with your Caterpillar dealer

CAT CONTROL PANELS

- Four levels of controls to meet individual customer needs:
 - EMCP II offers digital monitoring, metering, and protection
 - UL 508A Listed
 - EMCP II+ offers EMCP II features plus full-featured power metering and protective relaying
 - EMCP II+ Auto-Paralleling offers EMCP II+ features plus synchronization and load sharing
 - Switchgear conversion offers easy interface for remote switchgear
- UL 508A Listed

CAT SR4B GENERATOR

- Matched to the performance and output characteristics of Caterpillar engines
- Optimum winding pitch for minimum total harmonic distortion and maximum efficiency
- Segregated low voltage, AC/DC accessory box provides single point access to accessory connections
- UL 1446 Recognized Class H insulation

STANDBY 750 ekW 937 kVA

60 Hz 1800 rpm 480 Volts



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Single element canister type air cleaner • Service indicator 	<ul style="list-style-type: none"> • Dual element air cleaner • Heavy-duty air cleaner
Cooling	<ul style="list-style-type: none"> • Radiator with guard and duct flange • Coolant drain line with valve • Fan and belt guards • Caterpillar Extended Life Coolant • Low coolant level alarm or shutdown 	<ul style="list-style-type: none"> • Jacket water heater with shutoff valves • Heat exchanger and expansion tank
Exhaust	<ul style="list-style-type: none"> • Stainless steel exhaust flex and ANSI outlet flange 	<ul style="list-style-type: none"> • Mufflers (20, 25, or 30 dBA) • Elbow kit and through-wall installation kit • Manifold and turbocharger guards • All mufflers have side/end inlet options
Fuel	<ul style="list-style-type: none"> • Primary and secondary fuel filters • Water separator • Fuel priming pump • Flexible fuel lines • Fuel pressure gauge 	<ul style="list-style-type: none"> • Manual transfer pump • Choice of three Automatic Transfer Systems • Low fuel level alarm
Generator	<ul style="list-style-type: none"> • Permanent magnet excited • Class H insulation • Class F temperature rise (105°C prime/130°C standby) • VR6 Voltage Regulator, 3-phase sensing, 2:1 Volts/Hz • Reactive droop • Extension box • Bus bar connection 	<ul style="list-style-type: none"> • Self excited • Digital Voltage Regulator • Digital Voltage Regulator with KVAR/PF control • Anti-condensation space heater • Oversize and premium generators • Circuit breakers, UL Listed, 3-pole with shunt trip • Circuit breakers, IEC Compliant, 3-pole or 4-pole with shunt trip • Multiple breaker capability
Governor	<ul style="list-style-type: none"> • PEEC - Cat Electronic 	<ul style="list-style-type: none"> • Electronic isochronous • Electronic load sharing
Control Panels	<ul style="list-style-type: none"> • EMCP II 	<ul style="list-style-type: none"> • EMCP II+ • Switchgear conversion • Customer Communication Module • Local alarm and remote annunciator modules
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valves • Fumes disposal 	<ul style="list-style-type: none"> • Manual sump pump
Mounting	<ul style="list-style-type: none"> • Formed steel base • Linear vibration isolators between base and engine-generator 	<ul style="list-style-type: none"> • Integral fuel tank base • Sub base fuel tank • Wide base • Skid base
Starting/Charging	<ul style="list-style-type: none"> • 45 amp charging alternator • Energized to run (ETR) fuel shutoff solenoid • 24 volt starting motor • Batteries with rack and cables • Battery disconnect switch 	<ul style="list-style-type: none"> • Heavy-duty starting system • 5 or 10 amp battery charger • Oversize batteries • Ether starting aid
General		<ul style="list-style-type: none"> • Enclosures - sound attenuated, weather protective • Automatic transfer switches (ATS) • Floor standing circuit breakers • CSA Certification
Note	Standard and optional equipment may vary for UL 2200 Listed packages. UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics.	

STANDBY 750 ekW 937 kVA

60 Hz 1800 rpm 480 Volts



SPECIFICATIONS

CAT SR4B GENERATOR

Frame Size.....	596
Excitation.....	Permanent Magnet
Pitch.....	0.8666
Number of poles.....	4
Number of bearings.....	Single Bearing
Insulation.....	UL 1446 Recognized Class H with tropicalization and antiabrasion
IP Rating.....	Drip Proof IP22
Alignment.....	Pilot Shaft
Overspeed capability - % of rated.....	125
Wave form.....	Less than 5% deviation
Paralleling kit/Droop transformer.....	Standard
Voltage regulator.3 Phase sensing with selectable volts/Hz	
Voltage regulation.....	Less than +/- 1/2% (steady state) Less than +/- 1% (no load to full load)
Telephone Influence Factor.....	Less than 50
Harmonic distortion.....	Less than 5%

CAT DIESEL ENGINE

3412C TA V-12, 4-stroke-cycle watercooled diesel	
Bore - mm.....	137.20 mm (5.4 in)
Stroke - mm.....	152.40 mm (6.0 in)
Displacement - L.....	27.02 L (1648.76 cu. in)
Compression Ratio.....	14.5:1
Aspiration.....	TA
Fuel system.....	Scroll
Governor type.....	PEEC - Cat Electronic

CAT CONTROL PANELS

- EMCP II
- 24 Volt CD Control
- NEMA 1, IP22 enclosure
- Electronically dead front
- Lockable hinged door
- Generator instruments meet ANSI C-39-1
- Generator terminal box mounted
- Single location customer connection point
- UL508A Listed
- Panel illuminating lights
- Auto start/stop control
- Voltage adjust potentiometer
- True RMS AC metering
- Digital indications for:
 - rpm
 - Operating hours
 - Oil pressure
 - Coolant Temperature
 - System DC volts
 - AC volts, phase amps, Hz
- Shutdowns with indicating lights for:
 - Low oil pressure
 - High coolant temperature
 - Overspeed
 - Emergency Stop
 - Failure to start (overcrank)

STANDBY 750 ekW 937 kVA

60 Hz 1800 rpm 480 Volts



TECHNICAL DATA

Open Generator Set - - 1800 rpm/60 Hz/480 Volts	DM0635	
Package Performance Genset Power rating with fan Genset Power rating @ 0.8 pf	750 ekW 937.5 kVA	
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	206.4 L/hr 155.9 L/hr 109.8 L/hr	54.5 Gal/hr 41.2 Gal/hr 29.0 Gal/hr
Cooling System Air flow restriction (system) Engine coolant capacity	0.12 kPa 59.0 L	0.48 in. water 15.6 Gal
Exhaust System Combustion air inlet flow rate Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	65.2 m ³ /min 513.9 Deg C 181.9 m ³ /min 203.2 mm 6.7 kPa	2302.5 cfm 957 Deg F 6423.7 cfm 8.0 in 26.9 in. water
Heat rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	474 kW 794 kW 114 kW 34.97 kW	26956 Btu/min 45155 Btu/min 6483 Btu/min 1988.74 Btu/min
Alternator Motor starting capability @ 30% voltage dip Frame Temperature Rise	2255 skVA 596 130 Deg C	266 Deg F
Lube System Sump refill with filter	68.0 L	18.0 Gal

Ambient capability at 200 m (660 ft) above sea level. For ambient capability at other altitudes, consult your Caterpillar dealer.

UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

STANDBY 750 ekW 937 kVA

60 Hz 1800 rpm 480 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: ABGSM TM3, AS1359, AS2789, BS4999, BS5000, BS5514, DIN6271, DIN6280, EGSA101P, IEC34/1, ISO3046/1, ISO8528, JEM1359, NEMA MG 1-22, VDE0530, 89/392/EEC, 89/336/EEC

Standby - Output available with varying load for the duration of the interruption of the normal source power. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514. Standby ambients shown indicate ambient temperature at 100 percent load which results in a coolant top tank temperature just below the shutdown temperature.

Ratings are based on SAE J1995 standard conditions. These ratings also apply at ISO3046/1, DIN6271, and BS5514 standard conditions.

Fuel Rates are based on fuel oil of 35° API (16° C or 60° F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal).

Additional Ratings may be available for specific customer requirements. Consult your Caterpillar representative for details.

STANDBY 750 ekW 937 kVA

60 Hz 1800 rpm 480 Volts



DIMENSIONS

Package Dimensions		
Length	4514.3 mm	177.73 in
Width	1827.4 mm	71.94 in
Height	1990.3 mm	78.36 in
Weight	6704 kg	14,780 lb

Note: Do not use for installation design.
See general dimension drawings for
detail (Drawing #1863619).

Performance No.: DM0635

Feature Code:: 412DE1R

Source:: USA Sourced

1 December 2004

3601273

www.CAT-ElectricPower.com

©2004 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.